

## PRODUCT DATA SHEET

Standing: 2022-08-05

LAUDA Hydro H 24

Water bath 230 V; 50/60 Hz

Part Number: L002904

### Features

- Simple to operate water bath
- TFT display with clear display of all process data
- Setting and displaying temperature values in increments of 0.1°C.
- Setting the timer's time values in hours (h) and minutes (min).
- Membrane keypad with concise symbols
- Digital setpoint adjustment
- Adjustable trigger points for over- and under-temperature alarms up to max. +/- 10 K
- Temperature display can be switched from °C to °F
- 1-point temperature controller
- Optical and acoustic alarm for low-level and over/under temperature
- as well as for sensor break/short-circuit
- Electronic monitoring of the temperature controller
- Three application-specific timer functions.
- Bath interior, cover, sieve plate and heating element are made of stainless steel.
- Bath vessel with drain valve
- Heat insulating lid made of stainless steel, double-walled with inner curvature
- prevents condensate from dripping back into the vessels
- Lid and perforated tray as standard.



Working temperature min.  
25 °C



Working temperature max.  
100 °C

## PRODUCT DATA SHEET

Standing: 2022-08-05

LAUDA Hydro H 24

Water bath 230 V; 50/60 Hz

Part Number: L002904

### Technical Features

Working temperature range	25 ... 100 °C
Ambient temperature range	10 ... 40 °C
Temperature stability	0.1 ± K
Heater power max.	1.5 kW
Size of bath (W x D x H)	600 x 245 x 165 mm
Bath volume min. / max.	11.3 / 20.9 L
Overall dimensions (WxDxH)	700 x 440 x 275 mm
Weight	18 kg
Power supply	230 V; 50/60 Hz
Power plug	Power cord with angled plug (CEE7/7)

Reserve technical changes



[www.jointlab.com](http://www.jointlab.com)  
[www.frigolab.it](http://www.frigolab.it)

Via C. Treves 57, Trezzano sul Naviglio  
Milano, Italy  
+39.02.39310823  
[info@jointlab.com](mailto:info@jointlab.com)