

PRODUCT DATA SHEET

Standing: 2022-08-05

LAUDA Hydro H 41

Water bath 230 V; 50/60 Hz

Part Number: L002905

Features

- Simple to operate water bath
- TFT display with clear display of all process data
- Setting and displaying temperature values in increments of 0.1°C.
- Setting the timer's time values in hours (h) and minutes (min).
- Membrane keypad with concise symbols
- Digital setpoint adjustment
- Adjustable trigger points for over- and under-temperature alarms up to max. +/- 10 K
- Temperature display can be switched from °C to °F
- 1-point temperature controller
- Optical and acoustic alarm for low-level and over/under temperature
- as well as for sensor break/short-circuit
- Electronic monitoring of the temperature controller
- Three application-specific timer functions.
- Bath interior, cover, sieve plate and heating element are made of stainless steel.
- Bath vessel with drain valve
- Heat insulating lid made of stainless steel, double-walled with inner curvature
- prevents condensate from dripping back into the vessels
- Lid and perforated tray as standard.



Reserve technical changes



Working temperature min.
25 °C



Working temperature max.
100 °C

PRODUCT DATA SHEET

Standing: 2022-08-05

LAUDA Hydro H 41

Water bath 230 V; 50/60 Hz

Part Number: L002905

Technical Features

Working temperature range	25 ... 100 °C
Ambient temperature range	10 ... 40 °C
Temperature stability	0.1 ± K
Heater power max.	1.5 kW
Size of bath (W x D x H)	410 x 296 x 335 mm
Bath volume min. / max.	9.3 / 37.9 L
Overall dimensions (WxDxH)	510 x 490 x 476 mm
Weight	22 kg
Power supply	230 V; 50/60 Hz
Power plug	Power cord with angled plug (CEE7/7)

Reserve technical changes



www.jointlab.com

www.frigolab.it

Via C. Treves 57, Trezzano sul Naviglio

Milano, Italy

+39.02.39310823

info@jointlab.com